

## King™ Combination Nipples

**⚠ WARNING****Applications:**

- Recommended for low-pressure discharge and suction service for compatible liquids.  
**Sizes 1¼" and above are not for compressible products such as air or nitrogen.**
- **King™ Combination Nipples are not recommended for steam.**
- *The working pressure may vary with the construction of the hose, the type of clamping system used and the application. Consult Dixon™ for recommendations.*
- In accordance with the Association for Rubber Products Manufacturers (ARPM) bulletin for oil suction and discharge hose, a coupled length of hose in any size, should be tested to 1½ times the working pressure and held for fifteen minutes without leaking or coupling movement. For additional information and detailed instruction on testing procedures, see the Association for Rubber Products Manufacturers (ARPM) handbook.

## NPT threaded end with knurled wrench grip

Size	Opt Qty	Unplated Steel		Plated Steel		Brass		Aluminum	
		Part #		Part #		Part #		Part #	
½"	50	<b>ST1</b>		<b>STC1</b>		<b>BST1</b>		<b>AST1</b>	
¾"	50	<b>ST5</b>		<b>STC5</b>		<b>BST5</b>		<b>AST5</b>	
1"	50	<b>ST10</b>		<b>STC10</b>		<b>BST10</b>		<b>AST10</b>	
1¼"	50	<b>ST15</b>		<b>STC15</b>					
1½"	50	<b>ST20</b>		<b>STC20</b>					
2"	25	<b>ST25</b>		<b>STC25</b>					



knurled wrench grip

G

## NPT threaded end no knurl

Size	Opt Qty	Unplated Steel		Plated Steel		Brass		Aluminum	
		Part #		Part #		Part #		Part #	
1¼"	50	---				<b>BST15</b>		<b>AST15</b>	
1½"	50	---				<b>BST20</b>		<b>AST20</b>	
2"	25	---				<b>BST25</b>		<b>AST25</b>	
2½"	10	<b>ST30</b>		<b>STC30</b>		<b>BST30</b>		<b>AST30</b>	
3"	10	<b>ST35</b>		<b>STC35</b>		<b>BST35</b>		<b>AST35</b>	
4"	4	<b>ST40</b>		<b>STC40</b>		<b>BST40</b>		<b>AST40</b>	
5"	4	<b>ST50</b>		<b>STC50</b>				<b>AST50</b>	
6"	2	<b>ST60</b>		<b>STC60</b>				<b>AST60</b>	
8"	2	<b>ST80</b>		<b>STC80</b>					
10"	1	<b>ST100</b>		<b>STC100</b>					
12"	1	<b>ST120</b>		<b>STC120</b>					



no knurl brass

Size	Opt Qty	316 Stainless Steel		Hastelloy®	
		Part #		Part #	
½"	50	<b>RST1</b> <sup>1</sup>		---	
¾"	50	<b>RST5</b> <sup>1</sup>		---	
1"	50	<b>RST10</b>		---	
1¼"	50	<b>RST15</b>		---	
1½"	50	<b>RST20</b>		---	
2"	25	<b>RST25</b>		<b>HST25</b>	
2½"	10	<b>RST30</b>		---	
3"	10	<b>RST35</b>		<b>HST35</b>	
4"	4	<b>RST40</b>		---	
5"	4	<b>RST50</b>		---	
6"	4	<b>RST60</b>		---	
8"	2	<b>RST80</b>		---	



no knurl stainless

<sup>1</sup> made from investment casting

## King™ Combination Nipples

## Grooved end

## Features:

- Grooved and beveled ends (in *brass* and *aluminum*) are available in select sizes. Consult Dixon™ for prices and availability.
- See pages 744-750 for our complete line of groove style fittings.



Size	Unplated Steel		Opt Qty	316 Stainless Steel		Opt Qty
	Part #			Part #		
1"	<b>STV10</b>		50	---		---
1¼"	<b>STV15</b>		50	---		---
1½"	<b>STV20</b>		50	<b>RSTV20</b>		50
2"	<b>STV25</b>		25	<b>RSTV25</b>		25
2½"	<b>STV30</b>		10	---		---
3"	<b>STV35</b>		10	<b>RSTV35</b>		10
4"	<b>STV40</b>		4	<b>RSTV40</b>		5
5"	<b>STV50</b>		4	---		---
6"	<b>STV60</b>		4	---		---
8"	<b>STV80</b>		2	---		---
10"	<b>STV100</b>		1	---		---
12"	<b>STV120</b>		1	---		---

## Beveled end



Size	Unplated Steel		Opt Qty	316 Stainless Steel		Opt Qty	Aluminum	
	Part #			Part #			Part #	
½"	<b>STB1</b>		50	---		--	—	
¾"	<b>STB5</b>		50	<b>RSTB5</b>		50	—	
1"	<b>STB10</b>		50	<b>RSTB10</b>		50	<b>ASTB10</b>	
1¼"	<b>STB15</b>		50	<b>RSTB15</b>		50	<b>ASTB15</b>	
1½"	<b>STB20</b>		50	<b>RSTB20</b>		50	<b>ASTB20</b>	
2"	<b>STB25</b>		25	<b>RSTB25</b>		25	<b>ASTB25</b>	
2½"	<b>STB30</b>		10	<b>RSTB30</b>		10	<b>ASTB30</b>	
3"	<b>STB35</b>		10	<b>RSTB35</b>		10	<b>ASTB35</b>	
4"	<b>STB40</b>		4	<b>RSTB40</b>		4	<b>ASTB40</b>	
5"	<b>STB50</b>		4	---		--	<b>ASTB50</b>	
6"	<b>STB60</b>		2	<b>RSTB60</b>		--	<b>ASTB60</b>	
8"	<b>STB80</b>		2	<b>RSTB80</b>		--	<b>ASTB80</b>	
10"	<b>STB100</b>		1	---		--	<b>ASTB100</b>	
12"	<b>STB120</b>		1	---		--	—	

## BSPT Threaded end



Size	Plated Steel		Opt Qty	316 Stainless Steel		Opt Qty
	Part #			Part #		
1"	<b>STC10A</b>		50	<b>RST10A</b>		50
1¼"	<b>STC15A</b>		50	<b>RST15A</b>		50
1½"	<b>STC20A</b>		50	<b>RST20A</b>		50
2"	<b>STC25A</b>		50	<b>RST25A</b>		25
2½"	<b>STC30A</b>		10	<b>RST30A</b>		10
3"	<b>STC35A</b>		10	<b>RST35A</b>		10
4"	<b>STC40A</b>		4	<b>RST40A</b>		4
6"	<b>STC60A</b>		2	<b>RST60A</b>		2

## NPT end with knurled wrench grip - for plastic pipe



Size	Plated Steel		Opt Qty
	Part #		
½"	<b>SAP1</b>		50
¾"	<b>SAP6</b>		50
1"	<b>SAP11</b>		50
1¼"	<b>SAP16</b>		50
1½"	<b>SAP21</b>		50
2"	<b>SAP26</b>		25

## Jump Size King™ Combination Nipples

hose shank x NPT threaded end

Hose Shank	Male NPT	Plated Steel		316 Stainless Steel	
		Part #		Part #	
3/4"	1/2"	---		<b>RST0501</b>	
3/4"	1"	<b>STC0510</b>		<b>RST0510</b>	
1"	3/4"	<b>STC1005</b>		<b>RST1005</b>	
1"	1 1/4"	<b>STC1015</b>		<b>RST1015</b>	
1 1/4"	1"	<b>STC1510</b>		<b>RST1510</b>	
1 1/4"	1 1/2"	<b>STC1520</b>		<b>RST1520</b>	
1 1/2"	1 1/4"	<b>STC2015</b>		<b>RST2015</b>	
1 1/2"	2"	<b>STC2025</b>		<b>RST2025</b>	
1 3/4"	2"	<b>STC175200</b>		---	
2"	1 1/2"	<b>STC2520</b>		<b>RST2520</b>	
2"	2 1/2"	<b>STC2530</b>		---	
2"	3"	<b>STC2535</b>		<b>RST2535</b>	
2 1/2"	2"	<b>STC3025</b>		---	
2 1/2"	3"	<b>STC3035</b>		---	
3"	2"	<b>STC3525</b>		<b>RST3525</b>	
3"	2 1/2"	<b>STC3530</b>		---	
3"	4"	<b>STC3540</b>		---	
4"	3"	<b>STC4035</b>		---	



G

## Flanged King™ Combination Nipples

150# ASA flange x hose shank

Size	Steel		316 Stainless Steel	
	Standard	Designed for crimp-style sleeves or ferrules	Standard	Designed for crimp-style sleeves or ferrules
	Part #	Part #	Part #	Part #
1 1/2"	<b>FST20</b>	<b>FST20CS</b>	<b>RFST20</b>	<b>RFST20CS</b>
2"	<b>FST25</b>	<b>FST25CS</b>	<b>RFST25</b>	<b>RFST25CS</b>
3"	<b>FST35</b>	<b>FST35CS</b>	<b>RFST35</b>	<b>RFST35CS</b>
4"	<b>FST40</b>	<b>FST40CS</b>	<b>RFST40</b>	<b>RFST40CS</b>
6"	<b>FST60</b>	<b>FST60CS</b>	<b>RFST60</b>	<b>RFST60CS</b>
8"	<b>FST80</b>	---	<b>RFST80</b>	---
10"	<b>FST100</b>	---	<b>RFST100</b>	---
12"	<b>FST120</b>	---	<b>RFST120</b>	---



## Global King™ Combination Nipples

**⚠ WARNING**

### Applications:

- Combination nipples are recommended for low-pressure discharge and suction service for compatible liquids.
- Sizes 1 1/4" and above are not for compressible products such as air or nitrogen.**
- Global King™ Combination Nipples are not recommended for steam.**
- The working pressure may vary with the construction of the hose, the type of clamping system used and the application. Consult Dixon™ for recommendations.
- In accordance with the Association for Rubber Products Manufacturers (ARPM) bulletin for oil suction and discharge hose, a coupled length of hose in any size, should be tested to 1 1/2 times the working pressure and held for fifteen minutes without leaking or coupling movement. For additional information and detailed instruction on testing procedures, see the Association for Rubber Products Manufacturers (ARPM) handbook.

### Global hose shank x NPT threaded end

Size	Box Qty	Plated Steel	
		Part #	
1/2"	100	<b>GSTC1</b>	
3/4"	100	<b>GSTC5</b>	
1"	50	<b>GSTC10</b>	
1 1/4"	50	<b>GSTC15</b>	
1 1/2"	50	<b>GSTC20</b>	
2"	25	<b>GSTC25</b>	
2 1/2"	10	<b>GSTC30</b>	
3"	10	<b>GSTC35</b>	
4"	4	<b>GSTC40</b>	
5"	4	<b>GSTC50</b>	
6"	4	<b>GSTC60</b>	

