M1500 INS

EXPERT SERVICE LINE
BENCHTOP COUPLING INSERTER



KEY ADVANTAGES

- Compact
- Sturdy
- Powerful

MAIN APPLICATIONS

Dedicated to assemblers involved in relevant productions and professional workshops.

TECHNICAL SPECIFICATIONS

Dimensions: 750 x 660 x 300 mm (30 x 26 x 12") **Power Supply:** compressed air (7 bar)

Net Weight: 70 kg (154 lb) Techincal Features:

Capacity: 2wb: 2" max. Optional tool: for small bore 1/4", 3/4", 1/2" shell

4ws: 2" max. 6ws: 2" max.

HOSE AND FITTING SELECTION

Hose Type	Fittings Type	Max. Hose Size	Ref. Hoses
2 Wire Braid & Textile	MF2000 Multifit; MF3000 OPF; MF3000 OPK	2"	Tractor; Harvester; Lyteflex; Pilot; Cover; Equator; Rockmaster (braided); Shieldmaster (braided); Astro; Multitex; Hydroplast
4 Wire Spirals	MF2000 Multifit; MF2000 Interlock Plus; MF3000 OPK; MF2000 Spiralfit	2"	Rockmaster (spiral); Shieldmaster (spiral); GoldenISO Xtraflex
6 Wire Spirals	MF2000 Xtralock; MF2000 Interlock Plus	2"	Diamondspir (up to 2")





INSERT PUSHING MACHINES

M1500 INS

EXPERT SERVICE LINE

BENCHTOP COUPLING INSERTER

ORDERING INFORMATION

Product Code	Description	
EOI3430S1500I	M1500 INS (COUPLING INSERTER 1/2" to 2")	